

# THERMOSTAT WIRE, 18/6 UNSHIELDED CL2P




## DESCRIPTION

Thermostat Wire, Solid Bare Copper, 18/6, CL2P, ETL, PVC Jacket, 250 ft.

## FEATURES

- 18 AWG Solid Bare Copper Conductors
- Unshielded construction
- Plenum Fire Safety Rating (CL2P)
- Class 2 power-limited circuit cable for use in thermostat control applications
- Heat and moisture resistant insulation
- ETL Verified, RoHS Compliant
- Packaging: 250 ft Spool



<b>207-186/P/250WH</b>	Thermostat Wire, Unshielded, CL2P, 250ft, White
------------------------	---

<b>Conductor</b>	Solid Bare Copper
Size	18 AWG
	0.04 in. (1.02 mm ±0.01)
<b>Insulation</b>	PVC
Insulation Diameter	0.055 in. (1.4 mm ±0.1)
Average Thickness	0.007 in. (0.18 mm)
Minimum Thickness	0.0063 in. (0.16 mm)
Color	White, Red, Green, Blue, Yellow, Brown
<b>Rip Cord</b>	Yes
<b>Jacket</b>	PVC
Outer Diameter	0.19 in.
	(5.0 mm ±0.2)
Average Thickness	0.015 in. (0.38 mm)
Minimum Thickness	0.012 in. (0.30 mm)
Color	White
<b>Electrical &amp; Physical Properties</b>	
Conductor DCR @ 20°C	≤21.4Ω/km
Operating Temperature:	-20°C ~ 75°C
Voltage Rating	150 V
	(per NEC® Article 725)
Flame Test	CL2P
<b>Standards</b>	UL13, NEC® Article 725

### Marking on Jacket

VERTICAL 5024318 (ETL) CL2P THERMOSTAT CABLE 18AWG 6C  
XXXFT SUN RES ROHS RM# A B C D E F 1 2 3 4 5 6 7 8 9

### Weight

207-186/P/250WH	11 lbs
-----------------	--------

## VERTICAL CABLE

951.696.7772 California  
800.749.2447 Florida  
845.391.8318 New York  
713.322.7242 Texas



[www.verticalcable.com](http://www.verticalcable.com)

Rev. 07/2024

Subject to change without notice.