

# ALARM-SECURITY CABLE

## 22 AWG 2 CONDUCTOR

### SOLID CONDUCTORS SHIELDED



## DESCRIPTION

22 AWG 2 Conductor Solid Bare Copper, CM/CL2, Shielded with an overall jacket. 500 ft Pull Box

## APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Key Pads
- Smoke Detectors



## 210-222SO/S/5WH

### CONSTRUCTION

Conductor count:	2
Shape:	Round
Rip cord:	Yes
PE Tape:	Yes
Aluminum Foil:	Yes
Drain Wire (TC)	7/0.20

### CONDUCTORS

Material:	Bare solid copper
Trade size:	22 AWG
Conductor O.D.:	0.02 in. (0.61 mm)
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.04 in. (0.96 mm)
Insulation color:	Red, Black

### JACKET

Material:	Polyvinyl Chloride (PVC)
Thickness:	0.02 in. (0.45 mm)
O.D.:	0.1 in. (3.00 mm)
Marking:	VERTICAL 4001453 cETLUS CM/CL2 22AWG 2C SOLID SHIELDED 75C RoHS V1379P11444 XXXXFT

### MECHANICAL


Temperature rating:	75° C
---------------------	-------

### SAFETY

NFPA 70 (NEC®) rating:	CM/CL2
Voltage rating:	300 V RMS

### PACKED WEIGHT

210-222SO/S/5WH	6 lb
-----------------	------



## VERTICAL CABLE

951.696.7772 California  
800.749.2447 Florida  
845.391.8318 New York  
713.322.7242 Texas



[www.verticalcable.com](http://www.verticalcable.com)

Rev. 10/2024

Subject to change without notice.