

DIRECT BURIAL AUDIO CABLE

16 AWG 4 CONDUCTOR

CMX (UV) RATED



DESCRIPTION

16 AWG 4 Conductor Direct Burial, CMX (UV) Stranded Bare Copper, Unshielded with an overall jacket. 500 ft, Pull Box, Black.

APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications
- Suitable for Direct Burial
- Durable Weather Resistant Jacket
- UV Rated Outer Jacket



209-2316/DB

CONSTRUCTION

Conductor count:	4
Shape:	Round
Rip cord:	Yes
Water Block Tape:	Yes

CONDUCTORS

Material:	Stranded bare copper
Trade size:	16 AWG
Stranding:	65/0.16 mm
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.08 in. (2.10 mm)
Insulation color:	Red, Black, White, Green

JACKET

Material:	Polyethylene (PE)
Thickness:	0.04 in. (0.95 mm)
O.D.:	0.28 in. (7.00 mm)
Marking:	VERTICAL 5024318 c(ETL)us AUDIO CABLE 16AWG 4 COND 65 STRANDED OXYGEN FREE OUTDOOR UV DIRECT BURIAL RoHS 500FT 052327N0531107 19:39

MECHANICAL


Temperature rating:	75° C
Aging Condition (°Cxhrs):	100x168
Tensile Strength (Mpa)	
Before:	≥13.8
After:	≥85% of unaged
Aging Elongation (%)	
Before:	≥100
After:	≥50% of unaged
Cold Bend (-20±2° Cx4hrs):	No Crack

SAFETY

NFPA 70 (NEC®) rating:	CMX (UV)
Voltage rating:	300 V RMS

PACKED WEIGHT

209-2315/DB:	30 lb
--------------	-------



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York
713.322.7242 Texas



verticalcable.com

Rev. 12/2024

Subject to change without notice.