

Simply Connect.

DESCRIPTION

16 AWG 4 Conductor Stranded Bare Copper, Unshielded with an overall jacket. 500 ft, Pull Box, Purple.

APPLICATION

- Sound and Audio
- **Intercom Systems**
- **Indoor Applications**





AUDIO CABLE 16 AWG 4 CONDUCTOR STRANDED CABLE

209-2316/PR

CONSTRUCTION

Conductor count: Round Shape: Rip cord: Yes

CONDUCTORS

Stranded bare copper Material:

Trade size: **16 AWG** 65/0.16 mm Stranding:

Polyvinyl Chloride (PVC) 0.08 in. (2.10 mm) Red, Black, White, Green Insulation material:

Insulation O.D.: Insulation color:

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.50 mm)
O.D.: 0.25 in. (6.30 mm)
Marking: VERTICAL 5024318 c(ETL)us AUDIO CABLE
16AWG 4 COND 65 STRANDED OXYGEN

FREE CMR FT4 CL3R RoHS 500FT

080004N0711108 17:10

MECHANICAL

75° C Temperature rating: Aging Condition (°Cxhrs): 100x168

Tensile Strength (Mpa)

Before: ≥13.8

≥85% of unaged After:

Aging Elongation (%):

Before: ≥100

≥50% of unaged After:

Cold Bend

(-20±2° Cx4hrs): No Crack

SAFETY

NFPA 70 (NEC®) rating: CMR/CL3 300 V RMS

Voltage rating:

PACKED WEIGHT 209-2316/PR: 27 lb

> Jacket Rip Cord Conductor





VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

verticalcable.com