

## **DESCRIPTION**

16 AWG 4 Conductor Stranded Bare Copper, Unshielded with an overall jacket. 1000 ft, Spool, White.

## **APPLICATION**

- Sound and Audio
- **Intercom Systems**
- **Indoor Applications**



## **AUDIO CABLE 16 AWG 4 CONDUCTOR** STRANDED CABLE

## 209-2318

CONSTRUCTION

Conductor count:

Round Shape: Rip cord: Yes

**CONDUCTORS** 

Material: Stranded bare copper

Trade size: **16 AWG** 65/0.16 mm Stranding:

Polyvinyl Chloride (PVC) 0.08 in. (2.10 mm) Red, Black, White, Green Insulation material: Insulation O.D.:

Insulation color:

**JACKET** 

Material: Polyvinyl Chloride (PVC)
Thickness: 0.02 in. (0.50 mm)
O.D.: 0.25 in. (6.30 mm)
Marking: VERTICAL 5024318 c(ETL)us AUDIO CABLE
16AWG 4 COND 65 STRANDED OXYGEN
EREE SLIN RES CMP ET4 CL3B POLS

FREE SUN RES CMR FT4 CL3R RoHS

XXXXFT 052332N0531102 04:07

**MECHANICAL** 

Temperature rating: Aging Condition (°Cxhrs): 75° C 100x168

Tensile Strength (Mpa)

Before: ≥13.8

≥85% of unaged After:

Aging Elongation (%):

Before: ≥100

≥50% of unaged After:

Cold Bend

(-20±2° Cx4hrs): No Crack


**SAFETY** 

NFPA 70 (NEC®) rating: CMR/CL3 300 V RMS

Voltage rating:

PACKED WEIGHT

209-2318: 52.5 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

verticalcable.com