

DESCRIPTION

12 AWG 4 Conductor Stranded Bare Copper, Unshielded with an overall jacket. 500 ft, Spool, Black.

APPLICATION

- Sound and Audio
- **Intercom Systems**
- **Indoor Applications**





AUDIO CABLE 12 AWG 4 CONDUCTOR STRANDED CABLE

209-2319/BK

CONSTRUCTION

Conductor count:

Round Shape: Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: **12 AWG** 65/0.25 mm Stranding:

Polyvinyl Chloride (PVC) 0.08 in. (2.10 mm) Red, Black, White, Green Insulation material: Insulation O.D.:

Insulation color:

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.60 mm)
O.D.: 0.37 in. (9.50 mm)

Marking: VERTICAL 5024318 c(ETL)us AUDIO CABLE
12AWG 4 COND 65 STRANDED OXYGEN
FREE CMR FT4 CL3R RoHS XXXFT

040808N0427102 19:37

MECHANICAL

Temperature rating: Aging Condition (°Cxhrs): 75° C 100x168

Tensile Strength (Mpa)

Before: ≥13.8

After: ≥85% of unaged

Aging Elongation (%):

Before: ≥100

≥50% of unaged After:

Cold Bend

(-20±2° Cx4hrs): No Crack

SAFETY


NFPA 70 (NEC®) rating: CMR/CL3

Voltage rating:

300 V RMS

PACKED WEIGHT

209-2319/BK: 60.5 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

verticalcable.com