

Simply Connect.

## **DESCRIPTION**

14 AWG 4 Conductor Stranded Bare Copper, Unshielded with an overall jacket. 500 ft, Spool, White.

## **APPLICATION**

- Sound and Audio
- **Intercom Systems**
- **Indoor Applications**





## **AUDIO CABLE 14 AWG 4 CONDUCTOR** STRANDED CABLE

## 209-2326/WS/WH

CONSTRUCTION

Conductor count:

Round Shape: Yes Rip cord:

**CONDUCTORS** 

Material: Stranded bare copper

**14 AWG** Trade size: 105/0.16 mm Stranding:

Insulation material: Polyvinyl Chloride (PVC) 0.10 in. (2.60 mm) Insulation O.D.:

Insulation color: Red, Black, Green, White

**JACKET** 

Material: Polyvinyl Chloride (PVC)
Thickness: 0.03 in. (0.80 mm)
O.D.: 0.32 in. (8.00 mm)
Marking: VERTICAL 5024318 c(ETL)us AUDIO CABLE
14AWG 4 COND 105 STRANDED
OXYGEN FREE SUN RES CMR FT4 CL3

RoHS XXXFT

**MECHANICAL** 

Temperature rating: Aging Condition (°Cxhrs): Tensile Strength (Mpa) 75° C 100x168

Before: ≥13.8

≥85% of unaged After:

Aging Elongation (%):

≥100 Before:

≥50% of unaged After:

Cold Bend


(-20±2° Cx4hrs): No Crack

SAFETY

NFPA 70 (NEC®) rating: CMR/CL3 Voltage rating: 300 V RMS

PACKED WEIGHT

209-2326/WS/WH: 37.5 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

verticalcable.com