

## DESCRIPTION

14 AWG 4 Conductor Stranded Bare Copper, Unshielded with an overall jacket. 500 ft, Pull Box, White.

# APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications





#### VERTICAL CABLE 951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

# **AUDIO CABLE 14 AWG 4 CONDUCTOR** STRANDED CABLE

# 209-2326

#### CONSTRUCTION

Conductor count: Shape: Rip cord:

## CONDUCTORS

Material: Trade size: Stranding: Insulation material: Insulation O.D.: Insulation color:

4 Round Yes

Stranded bare copper 14 AWG 105/0.16 mm Polyvinyl Chloride (PVC) 0.10 in. (2.60 mm) Red, Black, Green, White

# JACKET

Material: Polyvinyl Chloride (PVC) Thickness: 0.03 in. (0.80 mm) O.D.: 0.32 in. (8.00 mm) Marking: VERTICAL 5024318 c(ETL)us AUDIO CABLE 14AWG 4 COND 105 STRANDED OXYGEN FREE SUN RES CMR FT4 CL3R RoHS XXXXFT 052333N0601102 01:40

### **MECHANICAL**

Temperature rating: Aging Condition (°Cxhrs): Tensile Strength (Mpa) 75° C Before: After: Aging Elongation (%): Before: After: Cold Bend (-20±2° Cx4hrs): SAFETY NFPA 70 (NEC®) rating:

Voltage rating: PACKED WEIGHT 209-2326:

100x168 ≥13.8

≥85% of unaged

≥100 ≥50% of unaged

No Crack

CMR/CL3 300 V RMS

37.5 lb

Jacket Insulation Rip Cord Conductor



### verticalcable.com

**Rev. 12/2024** Subject to change without notice.