

DESCRIPTION

18 AWG 2 Conductor Stranded Bare Copper. Unshielded with an overall jacket. 1000 ft, Pull Box, White

APPLICATION

- Sound and Audio
- **Intercom Systems**
- **Indoor Applications**





AUDIO CABLE 18 AWG 2 CONDUCTOR STRANDED CABLE

209-2327

CONSTRUCTION

2 Round Conductor count: Shape: Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

18 AWG Trade size: 16/0.24 mm Stranding:

Polyvinyl Chloride (PVC) Insulation material: 0.07 in. (1.75 mm) Insulation O.D.:

Red. Black Insulation color:

JACKET

Material: Polyvinyl Chloride (PVC) 0.02 in. (0.50 mm) Thickness:

O.D.: 0.19 in. (4.80 mm)

Marking: VERTICAL 4002107 c(ETL)us AUDIO CABLE

18AWG 2 COND 16 STRANDED OXYGEN

FREE CMR FT4 CL3R RoHS XXXXFT

88611M0203201 06:38

MECHANICAL

Temperature rating: Aging Condition (°Cxhrs): Tensile Strength (Mpa) 75° C 100x168

Before: ≥13.8

≥85% of unaged After:

Aging Elongation (%):

Before: ≥100

≥50% of unaged After:

Cold Bend


(-20±2° Cx4hrs): No Crack

SAFETY

NFPA 70 (NEC®) rating: CMR/CL3 Voltage rating: 300 V RMS

PACKED WEIGHT

23 lb 209-2327:







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

verticalcable.com