

DESCRIPTION

18 AWG 4 Conductor Stranded Bare Copper, Unshielded with an overall jacket. 500 ft, Pull Box, Black.

APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications





VERTICAL CABLE 951.696.7772 California 800.749.2447 Florida 845.391.8318 New York

845.391.8318 New Yo 713.322.7242 Texas

AUDIO CABLE 18 AWG 4 CONDUCTOR STRANDED CABLE

209-2329/BK

CONSTRUCTION

Conductor count: Shape: Rip cord:

CONDUCTORS

Material: Trade size: Stranding: Insulation material: Insulation O.D.: Insulation color: 4 Round Yes

Stranded bare copper 18 AWG 16/0.24 mm Polyvinyl Chloride (PVC) 0.07 in. (1.75 mm) Red, Black, Green, White

JACKET

Material: Polyvinyl Chloride (PVC) Thickness: 0.02 in. (0.50 mm) O.D.: 0.22 in. (5.60 mm) Marking: VERTICAL 524318 c(ETL)us AUDIO CABLE 18AWG 4 COND 16 STRANDED OXYGEN FREE CMR FT4 CL3R RoHS XXXFT 004907N0429207 01:01

MECHANICAL

Temperature rating: Aging Condition (°Cxhrs): Tensile Strength (Mpa) Before: After: Aging Elongation (%): Before: After: Cold Bend (-20±2° Cx4hrs):

NFPA 70 (NEC®) rating: Voltage rating: PACKED WEIGHT

209-2329/BK:

75° C 100x168


≥13.8 ≥85% of unaged

≥100 ≥50% of unaged

No Crack

CMR/CL3 300 V RMS

19 lb





verticalcable.com

Rev. 12/2024 Subject to change without notice.