

# AUDIO CABLE

## 16 AWG 2 CONDUCTOR

### STRANDED CABLE (SHIELDED)




#### DESCRIPTION

16 AWG 2 Conductor Stranded Bare Copper,  
Shielded with an overall jacket.  
500 ft, Pull Box, White.

#### APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications



#### 209-2355/S/5WH

##### CONSTRUCTION

Conductor count:	2
Shape:	Round
Rip cord:	Yes
PE Tape:	Yes
Drain Wire (TC):	7/0.20
Aluminum Foil:	Yes

##### CONDUCTORS

Material:	Stranded bare copper
Trade size:	16 AWG
Stranding:	65/0.16 mm
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.08 in. (2.10 mm)
Insulation color:	Red, Black

##### JACKET

Material:	Polyvinyl Chloride (PVC)
Thickness:	0.02 in. (0.60 mm)
O.D.:	0.22 in. (5.60 mm)
Marking:	VERTICAL 5024318 c(ETL)us AUDIO CABLE 16AWG 2 COND 65 STRANDED SHIELDED OXYGEN FREE CMR CL3R RoHS V2094P13592 XXXFT 73014M0924105 12:29

##### MECHANICAL


Temperature rating:	75° C
Aging Condition (°Cxhrs):	100x168
Tensile Strength (Mpa)	
Before:	≥13.8
After:	≥85% of unaged
Aging Elongation (%):	
Before:	≥100
After:	≥50% of unaged
Cold Bend (-20±2° Cx4hrs):	No Crack

##### SAFETY

NFPA 70 (NEC®) rating:	CMR/CL3
Voltage rating:	300 V RMS

##### PACKED WEIGHT

209-2355/S/5WH:	17 lb
-----------------	-------



## VERTICAL CABLE

951.696.7772 California  
800.749.2447 Florida  
845.391.8318 New York  
713.322.7242 Texas



verticalcable.com

Rev. 12/2024

Subject to change without notice.