

DESCRIPTION

22 AWG 4 Conductor Solid Bare Copper, CM/CL2, Unshielded with an overall jacket. 1000 ft, Pull Box, White.

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- **Kev Pads**
- Smoke Detectors



ALARM-SECURITY CABLE

22 AWG 4 CONDUCTOR SOLID CONDUCTORS

210-224S0/WH

CONSTRUCTION

Conductor count: 4

Shape: Round Rip cord: Yes

CONDUCTORS

Material: Solid bare copper

Trade size: 22 AWG

Conductor O.D.: 0.02 in. (0.61 mm)

Insulation material: Polyvinyl Chloride (PVC)

Insulation O.D.: 0.04 in. (0.96 mm)

Insulation color: Black, Red, White, Green

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.45 mm) O.D.: 0.12 in. (3.20 mm)

Marking: VERTICAL 5024318 c(ETL)us CM/CL2 22AWG

4C SOLID 75C SUN RES RoHS 116202N0918203 19:33 XXXXFT

MECHANICAL


Temperature rating: 75° C

SAFETY

NFPA 70 (NEC®) rating: CM/CL2 Voltage rating: 300 V RMS

PACKED WEIGHT

210-224SO/WH 14 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

verticalcable.com