

ALARM-SECURITY CABLE

22 AWG 4 CONDUCTOR
STRANDED (UNSHIELDED)




DESCRIPTION

22 AWG 4 Conductor Stranded Bare Copper,
CM/CL2, Unshielded with an overall jacket.
1000 ft, Pull Box, Grey

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Key Pads
- Smoke Detectors



210-224ST/GY

CONSTRUCTION

Conductor count:	4
Shape:	Round
Rip cord:	Yes

CONDUCTORS

Material:	Stranded bare copper
Trade size:	22 AWG
Conductor O.D.:	0.02 in. (0.61 mm)
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.04 in. (0.96 mm)
Insulation color:	Red, Black, White, Green

JACKET

Material:	Polyvinyl Chloride (PVC)
Thickness:	0.02 in. (0.45 mm)
O.D.:	0.1 in. (3.40 mm)
Marking:	VERTICAL 5024318 c(ETL)us CM/CL2 22AWG 4C STRANDED SHIELDED 75C SUN RES RoHS 080103N0717102 16:30 XXXXFT

MECHANICAL


Temperature rating:	75° C
---------------------	-------

SAFETY

NFPA 70 (NEC®) rating:	CM/CL2
Voltage rating:	300 V RMS

PACKED WEIGHT

210-224ST/GY	16 lb
--------------	-------



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York
713.322.7242 Texas



www.verticalcable.com

Rev. 12/2024
Subject to change without notice.