

ALARM-SECURITY CABLE

22 AWG 6 CONDUCTOR
STRANDED (UNSHIELDED)




DESCRIPTION

22 AWG 6 Conductor Stranded Bare Copper, CM/CL2, Unshielded with an overall jacket. 500 ft, Pull Box, White

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Key Pads
- Smoke Detectors



210-226ST/5WH

CONSTRUCTION

Conductor count:	6
Shape:	Round
Rip cord:	Yes

CONDUCTORS

Material:	Stranded bare copper
Trade size:	22 AWG
Diameter:	7 Strand (7x0.24mm)
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.04 in. (1.10 mm)
Insulation color:	Red, Black, White, Green, Blue, Brown

JACKET

Material:	Polyvinyl Chloride (PVC)
Thickness:	0.02 in. (0.45 mm)
O.D.:	0.17 in. (4.30 mm)
Marking:	VERTICAL 5024318 cETLus CM/CL2 22AWG 6C STRANDED 75C SUN RES RoHS 080105N0716203 18:48 XXXFT

MECHANICAL


Temperature rating:	75° C
---------------------	-------

SAFETY

NFPA 70 (NEC®) rating:	CM/CL2
Voltage rating:	300 V RMS

PACKED WEIGHT

210-226ST/5WH	12 lb
---------------	-------



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York
713.322.7242 Texas



www.verticalcable.com

Rev. 12/2024
Subject to change without notice.