

DESCRIPTION

22 AWG 8 Conductor Stranded Bare Copper, CM/CL2, Unshielded with an overall jacket. 500 ft, Pull Box, Grey

APPLICATION

- Intercom Systems
- **Security Systems**
- **Sound and Audio**
- **Power Limited Control Circuits**
- **Indoor Applications**
- **Door Controllers**
- **Kev Pads**
- **Smoke Detectors**



ALARM-SECURITY CABLE

22 AWG 8 CONDUCTOR **STRANDED (UNSHIELDED)**

210-228ST/5GY

CONSTRUCTION

Conductor count: 8

Round Shape: Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: **22 AWG**

Diameter: 7 Strand (7x0.24mm) Polyvinyl Chloride (PVC) Insulation material:

Insulation O.D.: 0.04 in. (1.10 mm) Red, Black, Green, Blue, Insulation color:

Brown, White, Orange, Yellow

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.50 mm) 0.19 in. (4.70 mm) O.D.:

Marking: VERTICAL 5024318 cETLus CM/CL2 22AWG

8C STRANDED 75C SUN RES RoHS

66912M0831102 19:30 XXXFT

MECHANICAL


Temperature rating: 75° C

SAFETY

NFPA 70 (NEC®) rating: CM/CL2 300 V RMS Voltage rating:

PACKED WEIGHT

210-228ST/5GY 15 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

www.verticalcable.com