

DESCRIPTION

22 AWG 8 Conductor Stranded Bare Copper, CM/CL2, Unshielded with an overall jacket. 500 ft, Pull Box, Grey

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Kev Pads
- Smoke Detectors



ALARM-SECURITY CABLE

22 AWG 8 CONDUCTOR STRANDED (UNSHIELDED)

210-228ST/GY

CONSTRUCTION

Conductor count: 8

Shape: Round Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: 22 AWG

Diameter: 7 Strand (7x0.24mm)
Insulation material: Polyvinyl Chloride (PVC)

Insulation O.D.: 0.04 in. (1.10 mm)
Insulation color: Red, Black, Green, Blue,

Brown, White, Orange, Yellow

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.50 mm) O.D.: 0.19 in. (4.70 mm)

Marking: VERTICAL 5024318 cETLus CM/CL2 22AWG

8C STRANDED 75C SUN RES RoHS

66913M0831102 16:53 XXXXFT

MECHANICAL


Temperature rating: 75° C

SAFETY

NFPA 70 (NEC®) rating: CM/CL2 Voltage rating: 300 V RMS

PACKED WEIGHT

210-228ST/GY 29 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

www.verticalcable.com