

DESCRIPTION

22 AWG 8 Conductor Stranded Bare Copper, CM/CL2, Shielded with an overall jacket. 500 ft Pull Box, Grey.

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Kev Pads
- Smoke Detectors



ALARM-SECURITY CABLE

22 AWG 8 CONDUCTOR STRANDED (SHIELDED)

210-228ST/S/5GY

CONSTRUCTION

Conductor count: 8

Shape: Round
Rip cord: Yes
PE Tape Yes
Drain Wire (TC) 7/0.20
Aluminum Foil Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: 22 AWG

Diameter: 7 Strand (7x0.24mm)
Insulation material: Polyvinyl Chloride (PVC)

Insulation O.D.: 0.04 in. (1.10 mm)

Insulation color: Red, Black, Green, Blue,

Brown, White, Orange,

Yellow

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.50 mm)
O.D.: 0.20 in. (5.10 mm)
Marking: VERTICAL 5024318 c(ETL)us CM/CL2

22AWG 8C STRANDED SHIELDED 75C SUN

RES RoHS 91910M1107201 XXXFT

MECHANICAL


Temperature rating: 75° C

SAFETY

NFPA 70 (NEC®) rating: CM/CL2 Voltage rating: 300 V RMS

PACKED WEIGHT

210-228ST/S/5GY 15 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

www.verticalcable.com