

DESCRIPTION

12 AWG 4 Conductor Stranded Bare Copper, CL3P, Unshielded with an overall jacket. 500 ft, Wooden Spool, White

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Kev Pads
- Smoke Detectors



ALARM-SECURITY CABLE 12 AWG 4 CONDUCTOR STRANDED PLENUM RATED

211-124/P/5WH

CONSTRUCTION

Conductor count: 4

Shape: Round Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: 12 AWG Stranding: 19 Strand

Strand Diameter: 0.02 in (0.47 mm)

Insulation material: Polyvinyl Chloride (PVC)

Insulation O.D.: 0.04 in. (1.10 mm)
Insulation color: Red. Black. White. Green

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.46 mm) O.D.: 0.31 in. (7.90 mm)

Marking: 12AWG*4C 75C 300V E499713 CMP (UL) C(UL)

OR E507553 CL2P&CL3P (UL) 10/14/2021

RoHS COMPLIANT XXXFT

MECHANICAL

Temperature rating: 75° C


DCR Conductor 5.41 Ohms/Km. @ 20°C

SAFETY

NFPA 70 (NEC®) rating: CMP/CL3P Voltage rating: 300 V RMS

PACKED WEIGHT

Wooden Spool: 19.7 lb (8.9 kg)





951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas



