

ALARM-SECURITY CABLE

14 AWG 2 CONDUCTOR
STRANDED PLENUM RATED



DESCRIPTION

14 AWG 2 Conductor Stranded Bare Copper, CL3P, Unshielded with an overall jacket. 1000 ft, Pull Box, White

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Key Pads
- Smoke Detectors



211-142/P/WH

CONSTRUCTION

Conductor count:	2
Shape:	Round
Rip cord:	Yes

CONDUCTORS

Material:	Stranded bare copper
Trade size:	14 AWG
Stranding:	19 Strand
Strand Diameter:	0.02 in (0.47 mm)
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.04 in. (1.10 mm)
Insulation color:	Red, Black

JACKET

Material:	Polyvinyl Chloride (PVC)
Thickness:	0.02 in. (0.46 mm)
O.D.:	0.20 in. (5.10 mm)
Marking:	14AWG 2C STRANDED c(ETL)us CMP 5024318 RoHS/FT6/CL3P 080109N0715103 03:52 XXXXFT

MECHANICAL


Temperature rating:	75° C
---------------------	-------

SAFETY

NFPA 70 (NEC®) rating:	CMP/CL3P
Voltage rating:	300 V RMS

PACKED WEIGHT

211-142/P/WH (Spool):	37.8 lb
-----------------------	---------



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York
713.322.7242 Texas



www.verticalcable.com

Rev. 12/2024
Subject to change without notice.