

# ALARM-SECURITY CABLE

14 AWG 4 CONDUCTOR

STRANDED PLENUM RATED



## DESCRIPTION

14 AWG 4 Conductor Stranded Bare Copper, CL3P, Unshielded with an overall jacket. 500 ft, Pull Box, White

## APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Key Pads
- Smoke Detectors



## 211-144/P/5WH

### CONSTRUCTION

Conductor count:	4
Shape:	Round
Rip cord:	Yes

### CONDUCTORS

Material:	Stranded bare copper
Trade size:	14 AWG
Stranding:	19 Strand
Strand Diameter:	0.02 in (0.47 mm)
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.04 in. (1.10 mm)
Insulation color:	Red, Black, Green, White

### JACKET

Material:	Polyvinyl Chloride (PVC)
Thickness:	0.02 in. (0.46 mm)
O.D.:	0.24 in. (6.20 mm)
Marking:	14AWG 4C STRANDED c(ETL)us CMP5024318 RoHS/FT6/CL3P 91804M1111203 02:35 XXXFT

### MECHANICAL


Temperature rating:	75° C
---------------------	-------

### SAFETY

NFPA 70 (NEC®) rating:	CMP/CL3P
Voltage rating:	300 V RMS
DC Resistance per Conductor:	@ 20° C 2.6Ω/1m'
Maximum pulling tension:	168lbs
Min. Bend Radius:	2vv .6 in

### PACKED WEIGHT

211-144/P/5WH:	19.7 lb
----------------	---------



**VERTICAL CABLE**

951.696.7772 California

800.749.2447 Florida

845.391.8318 New York

713.322.7242 Texas

[www.verticalcable.com](http://www.verticalcable.com)

Rev. 12/2024

Subject to change without notice.