

# ALARM-SECURITY CABLE

18 AWG 2 CONDUCTOR

DIRECT BURIAL/OUTDOOR RATED



## 211-182ST/S/DB

### CONSTRUCTION

Shape	Round
Rip Cord	Yes
Core Wrap	PE Tape
Drain Wire Material	TC
Drain Wire Size	0.3 X 0.008 in. (7 X 0.2 mm ±0.01)
Shield	AL/PET Foil
Filler	Water Proof Tape

### CONDUCTORS

Material	Stranded Bare Copper
Trade size	18 AWG
Conductor Count:	2
Size	0.63 X 0.0098 in. (16 X 0.25 mm ±0.01)

### INSULATION

Material	Polyvinyl Chloride (PVC)
Min. Thickness	0.008 in. (0.21 mm)
Avg. Thickness	0.01 in. (0.26 mm)
Diameter	0.067 in. (1.7 mm ±0.1)
Color	Red, Black

### JACKET

Material	PE
Avg. Thickness	0.024 in. (0.60 mm)
Min. Thickness	0.019 in. (0.50 mm)
Diameter	0.21 in. (5.4 mm ±0.3)
Color	Black
Marking:	VERTICAL 5024318 c(ETL)us 18 AWG 2C STRANDED SHIELDED PE JKT CMX OUTDOOR / DIRECT BURIAL RoHS XXXXFT 080116N0730204 10:24

### ELECTRICAL & PHYSICAL

Temperature Rating	-20°C to +70°C
Resistacne	UV
Voltage Rating	300 V RMS
Nom. Conductor DCR	≤22.5 Ohm/km

### PACKED WEIGHT


211-182ST/S/DB	23.3 lb
----------------	---------

## DESCRIPTION

18 AWG 2 Conductor Stranded Bare Copper,  
Direct Burial. Overall Foil-Shielded Construction.  
1000 ft, Pull Box, Black

## APPLICATION

- Overall Foil-Shielded Construction
- Easily Identified Colors
- 18 AWG Stranded Bare Copper Conductors
- Outdoor Applications
- ETL-Listed, RoHS Compliant



**VERTICAL CABLE**

951.696.7772 California

800.749.2447 Florida

845.391.8318 New York

713.322.7242 Texas



[www.verticalcable.com](http://www.verticalcable.com)

Rev. 11/2024

Subject to change without notice.