

DESCRIPTION

18 AWG 6 Conductor Stranded Bare Copper, Shielded with an overall jacket. 1000 ft, Wooden Spool, Grey

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Kev Pads
- Smoke Detectors



ALARM-SECURITY CABLE

18 AWG 6 CONDUCTOR STRANDED (SHIELDED)

211-186ST/S/GY

CONSTRUCTION

Conductor count: 6

Shape: Round
Rip cord: Yes
PE Tape: Yes
Drain Wire (TC): 7/0.20
Aluminum Foil: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: 18 AWG Stranding: 16/0.24 mm

Strand Diameter: 0.02 in (0.47 mm)

Insulation material: Polyvinyl Chloride (PVC)

Insulation O.D.: 0.07 in. (1.7 mm)

Insulation color: Red, Black, White, Green,

Brown, Blue

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.5 mm) O.D.: 0.25 in. (6.4 mm)

Marking: Vertical 5024318 c(ETL)us CM/CL2 18AWG 6C

STRANDED SHIELDED 75C SUN RES ROHS

097820N0810206 XXXXFT

MECHANICAL


Temperature rating: 75° C

SAFETY

Voltage rating: 300 V RMS

PACKED WEIGHT

211-186ST/S/GY: 55 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

www.verticalcable.com