

DESCRIPTION

22 AWG 4 Conductor Stranded Bare Copper, Unshielded with an overall jacket, Coil Pack, 500 ft, White

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Kev Pads
- Smoke Detectors



ALARM-SECURITY CABLE 22 AWG 4 CONDUCTOR STRANDED CABLE

212-224ST/5WH

CONSTRUCTION

Conductor count: 4

Shape: Round Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: 22 AWG Stranding: 7/0.24 mm

Insulation material: Polyvinyl Chloride (PVC)

Insulation O.D.: 0.04 in. (1.10 mm)

Insulation color: Red, Black, Green, White

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.45 mm) O.D.: 0.14 in. (3.60 mm)

Marking: VERTICAL 5024318 c(ETL)us CMR/CL2R

22AWG 4C STRANDED 75C SUN RES RoHS

22711N0403103 10:38 XXXFT

MECHANICAL


Temperature rating: 75° C

SAFETY

NFPA 70 (NEC®) rating: CM/CL2 Voltage rating: 300 V RMS

PACKED WEIGHT

212-224ST/5WH: 7 lb





951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas





www.verticalcable.com