

CAT5E CELL TOWER CABLE

CMX / UV-RESISTANT / DIRECT BURIAL

24 AWG 8 CONDUCTOR (F/UTP)



DESCRIPTION

350 MHz CAT5E Cell Tower Cable, Outdoor Dual Jacket, Direct Burial / CMX / Shielded, 4 Twisted Pairs (F/UTP) 8 24-AWG Solid Bare Copper Conductors.

FEATURES

- Supports 10/100/1000BASE-T applications
- Outdoor UV-resistant
- Cell Tower / Direct Burial
- Aluminum Foil protects from EMI/RFI
- 350-MHz bandwidth supporting wide range of applications
- 24 AWG Solid Copper Conductors
- Easily identifiable pair insulation colors
- Exceeds ANSI/TIA-568.2-D and ISO/IEC 11801 specifications
- CAN/CSA-C22.2 No. 214, RoHS compliant
- ETL listed



059-494/WS/CWT

TRANSMISSION PERFORMANCE

Meets or exceeds ANSI/TIA-568.2-D and ISO/IEC 11801 specifications

CONSTRUCTION

Pairs: 4
 Conductors: 8
 Rip Cord: 1
 Drain Wire (Tinned Copper): 0.016 in. (0.40 mm)
 Screen: Foiled (F/UTP)

CONDUCTORS

Material: Solid Bare Annealed Copper
 Size: 24 AWG

INSULATION

Material: PE
 Diameter: 0.04 in. (0.91 mm)
 Average thickness: 0.0078 in (0.20 mm)
 Min. point thickness: 0.0074 in. (0.19 mm)
 Color coding: **Pair 1:** White-Blue/Blue **Pair 2:** White-Orange/Orange
Pair 3: White-Green/Green **Pair 4:** White-Brown/Brown

INNER JACKET (GRAY)

Material: Polyethylene (PE)
 Outer diameter: 0.19 in. (4.80 mm)
 Average thickness: 0.0157 in. (0.40 mm)
 Min. point thickness: 0.0141 in. (0.36 mm)

OUTER JACKET (BLACK)

Material: Linear Low Density Polyethylene (LLDPE)
 Outdoor rating: UV-resistant
 Outer diameter: 0.26 in. (6.60 mm)
 Average thickness: 0.0275 in. (0.70 mm)
 Min. point thickness: 0.0212 in. (0.54 mm)
 Marking: VERTICAL 4001453 cETLus VERIFIED CMX F/UTP 4PR 24AWG
 OUTDOOR CELL TOWER & DIRECT BURIAL UV LLDPE CAT5E
 350MHz ANSI/TIA-568.2-D RoHS V1379P12760 XXXXFT

ELECTRICAL

Voltage rating: 60 VRMS

MECHANICAL

Before Tensile Strength (Mpa): ≥ 13.8 MPa
 Elongation After Aging (%): ≥ 100
 Aging Conditions ($^{\circ}$ C \times h): 100x168
 Tensile Strength After Aging (Mpa): $\geq 85\%$ of unaged
 Elongation After Aging (%): $\geq 50\%$ of unaged
 Cold Bend ($-40 \pm 2^{\circ}$ Cx4hrs): No Crack

SAFETY



FPA 70 (NEC®) fire rating: CMX

ENVIRONMENTAL

Operating temperature: -40° F– 167° F (-40° C– 75° C)

WEIGHT

30.6 lb (13.6 kg)



VERTICAL CABLE

951.696.7772 California
 800.749.2447 Florida
 845.391.8318 New York
 713.322.7242 Texas



verticalcable.com

Rev. 01/2025

Subject to change without notice.