

Simply Connect.

DESCRIPTION

2-Port Surface Mount Box with a CAT6A RJ45 built-in jack, White

FEATURES

- High-impact ABS construction
- Screws, ties and adhesive tape included
- Can be terminated with 110 or Krone type tools
- UL 94V-0 Fire Retardant
- Gloss finish
- UL listed
- ISO/IEC 11801, ANSI/TIA-568.2-D Compliant



SURFACE MOUNT BOX WITH 2-PORT CAT6A RJ45 JACK

038-C6A/2P/WH

SPECIFICATIONS

MATERIAL

Case: ABS, UL 94V-0
Metal Cover: SECC, 0.6 mm thickness
RJ45 Jack Shield: Bronze with nickel plated finish
RJ45 Jack Housing: PBT+Glass Fiber, UL 94V-0
Contact Bracket: PBT+Glass Fiber, UL 94V-0

RJ45 JACK CONTACT

Material: Phospor Bronze with Nickel plating Finish: 50 μ" Gold plating on Plug contact area

IDC

Housing: PC + Glass Fiber, UL 94V-2
Terminal: Phosper Bronze with Tin plating

PCB FR4, UL 94V-0

Screw: M2.0 x 6.0 x ø 3.3mm

"U" Clip: Bronze with nickel plated finish

0.5 mm thickness

Insertion Force: 30N Max. (IEC 60603-7-4)


Retention Force: 17 lb (7.7 kg) between jack and plug


Operating Temp.: -10° C to 60° C max

PERFORMANCE

Meets or exceeds ISO/IEC 11801,

ANSI/TIA-568.2-D







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

verticalcable.com