

IP-Rated Boxes

253-SMB67-A0	Surface-Mount Box, Blank/Unported, IP66/67
253-SMB67-A1	Surface-Mount Box, 1-Port – 1-Left-In 1-Left-Out, Blank, IP66/67
253-SMB67-A2	Surface-Mount Box, 2-Port – 2-Left-In/2-Right-Out, Blank, IP66/67
253-SMB67-A3	Surface-Mount Box, 1-Port – 1-Left-In/1-Top-Out, Blank, IP66/67
253-SMB67-A4	Surface-Mount Box, 2-Port – 2-Left-In/2-Top-Out, Blank, IP66/67

Made-to-order hole configurations are available.

KITTING


As-delivered:

- ✔ 1×base (with integral sealing gasket);
- ✔ 1×cover;
- ✔ 4×cover screws;
- ✔ 4×wood screws for surface mounting;
- ✔ 4×cover screw hole plugs.

Not included:

- ❌ outlet modules;
- ❌ cable glands;
- ❌ blank plugs.

253-SMB67-A0



ACCESSORIES

259-SLC01-FOC1	Cable Gland, M16, Plastic, 5-mm–10-mm Cable O.D.,
259-SLC01-FOA1	Cable Gland, M16, Plastic, 2-mm–3-mm Cable O.D., Simplex**
259-SLC01-FOA2	Cable Gland, M16, Plastic, 2-mm–3-mm Cable O.D., Duplex***

- * Recommended for round twisted-pair and optical fiber cables.
- ** Recommended for simplex round optical fiber cables.
- *** Recommended for duplex zipcord optical fiber cables.

250-IOM68-A000	Blank Plug for Outlet Opening, IP68
259-SLC02-B0F	Blank Plug for Cable Gland Opening, IP68

250-IOM68-A000



259-SLC02-B0F



CHARACTERISTICS

Compatibility:	250-IOM68 Outlet Modules.
Material:	ABS UL 94 V-0.
Environmental protection:	IP66/67.
Impact protection:	IK07.
Compliance:	IEC 60529; UL 1863.
Cable gland IP rating:	IP68.
Cable gland cable size:	5 mm–10 mm O.D. round twisted-pair cables; 2 mm–3 mm O.D. round optical fiber cables; 2 mm–3 mm O.D. optical fiber zipcords.
Dimensions:	122 mm × 120 mm × 80 mm (4.8 in × 4.7 in × 3.2 in) without outlets and glands.

