

RG6 STANDARD SHIELD

18 AWG

COAXIAL CABLE (CM-RATED)



DESCRIPTION

**RG6 Standard Shield (Dual),
18 AWG Solid CCS Conductor,
Aluminum Foil with 60% Braid.**

FEATURES

- High-Grade RG6 Coaxial Cable
- Fully Sweep-Tested to 3000MHz
- 18AWG Solid Copper-Clad Steel
- CMR, CATV, CL2
- ETL, RoHS Compliant
- Supplied in 1000ft Pull Box



107-1957WH6SR

CONSTRUCTION

Conductor count:	1
Shape:	Round
Braid:	60% Aluminum
Aluminum Foil:	Yes
Aluminum Foil Shield:	Bonded

CONDUCTORS

Material:	Copper Clad Steel
Trade size:	18 AWG
Insulation material:	Dielectric Foam PE
Insulation O.D.:	0.18 in. (4.60 mm)
Insulation color:	White

JACKET

Material:	Polyvinyl Chloride (PVC)
O.D.:	0.27 in. (6.90 mm)
Marking:	c(ETL)us 5024318 CMR RG6 18AWG 60% 3.0GHz CMG FT4 CATV/CL2 RoHS V2094P13881 XXXXFT 059811N0603104 09:07

MECHANICAL


Temperature rating:	75° C
Sparker Test:	3000VAC
Impedance:	75 Ohm
Capacitance:	52 pF/m
Velocity of Propagation:	85%
Return Loss:	23 dB Min (5-2300 MHz)
Bending Radius:	2.56 in. (65 mm)
Sweep Test:	3.0 GHz
DC Resistance:	(<) 120 Ohms/km

SAFETY

NFPA 70 (NEC®) rating:	CMX/CL2
Voltage rating:	300 V RMS

PACKED WEIGHT

107-1957WH6SR:	28 lb (12.7 kg)
----------------	-----------------



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York
713.322.7242 Texas



verticalcable.com

Rev. 04/2025

Subject to change without notice.