












COMPONENTS & ACCESSORIES



Modular Components

Epoxy Plugs

Plug type			SM UPC	SM APC	OM3	OM4
FC			263-OFC01-1BZx 	263-OFC01-1BYx 		
ST			263-OFC02-1BZx 			
SC	SX		263-OFC03-1BZx 	263-OFC03-1BYx 	263-OFC03-1BCx 	
	DX		263-OFC03-2BZx 	263-OFC03-2BYx 	263-OFC03-2BCx 	
LC	SX	STD	263-OFC04-1BZx 	263-OFC04-1BYx 	263-OFC04-1BCx 	263-OFC04-1BDx 
	DX	STD	263-OFC04-2BZx 	263-OFC04-2BYx 	263-OFC04-2BCx 	263-OFC04-2BDx 
	UNI		263-OFC04-3BZx 	263-OFC04-3BYx 	263-OFC04-3BCx 	263-OFC04-3BDx 

Plugs of other colors are available as special orders, minimum order quantity – 100 plugs of each color.

Substitute "x" in PN

with:

"01": 1-pack;

"12": 12-pack;



STANDARD



UNIBODY

CHARACTERISTICS

	FC		ST	SC			LC			
	SM UPC	SM APC	SM UPC	SM UPC	SM APC	OM3	SM UPC	SM APC	OM3	OM4
Body color:	—	—	—	●Blue	●Green	●Aqua	●Blue	●Green	●Aqua	●Violet
Boot color	●Blue	●Green	●Blue	●Blue	●Green	○White	○White	○White	○White	○White
DX clip color	—	—	—	●Black	●Black	●Black	●Blue	●Green	●Aqua	●Violet
Bore size:	125.5 μm	125.0 μm	125.5 μm	125.5 μm	125.0 μm	126.0 μm	125.5 μm	125.0 μm	126.0 μm	126.0 μm
Concentricity:	1.0 μm					4.0 μm	1.0 μm		4.0 μm	
Curvature radius:	10–25 mm						7–25 mm			
Apex offset:	0–50 μm									
Fiber height:	50–100 nm									
Cable diameter:	0.9 mm									
Boot size:	0.9 mm									
Insertion loss*:	≤0.3 dB									
Return loss*:	≥55 dB	≥65 dB	≥55 dB	≥55 dB	≥65 dB	≥35 dB	≥55 dB	≥65 dB	≥35 dB	≥35 dB
Compatibility:	Telcordia GR-326-CORE									
Compliance:	IEC 61754-13		IEC 61754-2		IEC 61754-4			IEC 61754-20		
	Regulation (EC) No 1907/2006 (REACH); Directive 2011/65/EU Am. 2015/863/EU (RoHS2); UL 94 V-0									

* When polished following industry's best practices.