



ALARM-SECURITY CABLE

18 AWG 6 CONDUCTOR

STRANDED (PLENUM-RATED)

211-186ST/P/WH

CONSTRUCTION

Conductor count:	6
Stranding:	19 Strand
Strand Diameter	19 x 0.01 in. (0.235±0.01 mm)
Shape:	Round
Rip cord:	Yes

CONDUCTORS

Material:	Stranded bare copper
Trade size:	22 AWG
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.07 in. (1.70±0.1 mm)
Avg. Thickness:	0.01 in. (0.22 mm)
Min. Thickness:	0.01 in. (0.18 mm)
Insulation color:	Black, Red, White, Green, Blue, Brown

JACKET

Material:	Polyvinyl Chloride (PVC)
O.D.:	0.23 in. (5.90±0.20 mm)
Avg. Thickness:	0.01 in. (0.38 mm)
Min. Thickness:	0.01 in. (0.30 mm)
Color:	White
Marking:	18AWG 6C STRANDED UNSHIELDED c(ETL)us CMP 5024318 RoHS/FT6/CL3P 22731800113103 XXXFT

MECHANICAL

Temperature rating:	-20°C ~ +75°C
---------------------	---------------

SAFETY

Nom. DCR Conductor:	≤21.9 Ohm/km
Voltage rating:	300 V
Fire Test:	CMP

PACKED WEIGHT


211-186ST/P/WH:	XXX lb
-----------------	--------

DESCRIPTION

18/6 Stranded Bare Copper Conductors, Unshielded with an overall jacket. Plenum Rated (CMP), 1000 ft Pull Box

FEATURES

- 18 AWG, 6-Conductor Stranded Bare Copper
- Plenum-Rated (CMP) Unshielded Construction
- Rip Cord Included
- Color-Coded Conductors (Black, Red, White, Green, Blue, and Brown)
- 1000 ft Wooden Spool
- ETL Listed, RoHS Compliant, FT6 Rated



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York
713.322.7242 Texas



verticalcable.com

Rev. 05/2025

Subject to change without notice.