

Surface- and Wall-Mount Enclosures

Adapter Plate Enclosures - EZX & EZV Series

EZ-Xcess Series



Model with Cam Latch

268-EZX01-1A1L1


Optical Fiber Wall-Mount Enclosure, LGX, Solid Door, Cam Latch, comes with "L" type Blank Bracket & Large Grommet Cable Entry Adapters.



Base

Includes:

- base
- cover
- cam latch
- FM spools
- label holder
- blank cable entry bracket
- large grommet cable entry bracket



"L" Blank
"L" Large Grommet

EZ-View Series



Model with Cam Latch

268-EZV01-1A1L1


Optical Fiber Wall-Mount Enclosure, LGX, Viewport Door, Cam Latch, comes with "L" type Blank Bracket & Large Grommet Cable Entry Adapters.



Base

Includes:

- base
- cover
- cam latch
- FM spools
- label holder
- blank cable entry bracket
- large grommet cable entry bracket



"L" Blank
"L" Large Grommet

Surface- and Wall-Mount Enclosures

Adapter Plate Enclosures - EZX & EZV Series



CHARACTERISTICS

Adapter plate format: LGX.	
Capacity:	adapter plates: 1; fibers: up to 24; splices: up to 24.
Access:	single door, cam latch (Southco® brand hardware).
Mounting:	surface/wall, left- or right-hand independent.
Cable management:	cable entry port adapters (ordered separately); cable anchor points (bridge lances); set of cable ties and Velcro® tie wraps.
Fiber management:	FM spools (default); FM stage (optional).
Labeling:	removable label holder, plain paper inserts.
Materials:	1.5-mm (15-GA) aluminum alloy; black powder coating.
Threaded joints:	SI (metric).
Mechanical:	cam latch average ultimate load: 180 N (40.5 lbf); recommended mounting nut tightening torque: 5 N-m (44 pfi) max; recommended pawl screw tightening torque: 4 N-m (35 pfi) max; cycle life: 25,000 cycles at no load.
Environmental:	operating temperature: -20 °C–+70 °C (-4 °F–+158 °F); operating humidity: ≤95 % RH non-condensing.
Dimensions:	Width: 280 mm (11 in); Height: 180 mm (7 in); Depth: 50 mm (2 in) without protruding parts of latch ("box" only).
Weight:	2 lbs

Accessories/Fiber Management for EZ-Xcess and EZ-View Series





- 268-ACC03-11-00 Splicing Stage, No Splice Protection Sleeves, No Splice Holders.
 265-HLD01-2B-00 Optical Fiber Splice Holder, Adhesive Mounting, No Sleeves, 12-Fiber Capacity.
 265-SLV01-3A-1H Optical Fiber Splice Protection Sleeve, 2.5 mm×40 mm, pack of 100.



268-ACC03-11-00

Cable entry adapters for EZ-Xcess and EZ-View Series

EZX and EZV enclosures, excluding "blank-box" configurations, are supplied with one blank and one specialized cable entry adapter brackets. Cable entry adapter brackets may be ordered separately, adding flexibility in creating configurations per project requirements:

	BLANK	RUBBER GROMMETS			CABLE GLANDS			MPO ADAPTERS			
"L" type											
	268-ACC01-1A0	268-ACC01-1B1	268-ACC01-1C1	268-ACC01-1D1	268-ACC01-1E1	268-ACC01-1F1	268-ACC01-1G1				
"M" type											
	268-ACC01-2A0		268-ACC01-2B1	268-ACC01-2C1	268-ACC01-2H1	268-ACC01-2I1	268-ACC01-2J1	268-ACC01-2D1	268-ACC01-2E1	268-ACC01-2F2	268-ACC01-2G2
		for cables with external diameters:			for cables with external diameters:			connector type:			
		≤20 mm (≤0.8 in)	≤12 mm (≤0.5 in)	≤8 mm (≤0.3 in)	2 mm–6.5 mm (0.08 in–0.25 in)	3 mm–8 mm (0.12 in–0.32 in)	5 mm–12 mm (0.20 in–0.47 in)	MPO adapter, Type A, compact, flanged, black			
		grommet material:			gland form-factor:			count:			
		TPE (thermoplastic elastomer), UL 94 V-2			M12	M16	M20	1		2	
					gland material:			connector mounting orientation:			
					PA/CR (polyamide/Neoprene)			lateral	transversal	lateral	transversal
	bracket material: 1.5-mm (15-GA) aluminum alloy bracket finish: powder coating, black (RAL 9005) mounting: four M3 CSK machine screws (included) packing: individual PE bag										