

OSP Tension Clamps	269-OPH02-80702	269-OPH02-80902	269-OPH02-D10P7	269-OPH02-D11P2
				
Cable construction:	Self-supporting drop "8 in, fiber-reinforced plastic (FRP) or aramid yarn messenger		FTTH drop (flat drop cable)	
Cable/messenger OD diameter:	3 mm–7 mm (0.12 in–0.3 in)	6 mm–9 mm (0.25 in–0.35 in)	3 mm–5 mm (0.12 in–0.2 in)	3 mm–7 mm (0.12 in–0.3 in)
Load capacity:	2 kN (~450 lbf)		0.7 kN (~160 lbf)	1.2 kN (~270 lbf)
Cable retention mechanism:	Tension, self-adjusting wedges		Tension, wedge, and perforated shim	
Material:	Fiberglass-reinforced plastic		Stainless steel Type 201	
Length:	—	—	150 mm (8.7 in)	220 mm (8.7 in)
Bail material:	Stainless steel			
Bail length:	230 mm (9 in)			
Operating temperature:	-60 °C–+60 °C (-76 °F–+140 °F)			
Mounting:	Wall or pole using clamp anchor points (brackets)			
Applications:	Dead-end support/drop			

OSP Brackets	269-OPH10-0115	269-OPH10-0304
	 	 
Load capacity:	15 kN (~3,370 lbf)	5 kN (~1,120 lbf)
Material:	Aluminum alloy	
Dimensions:	116 mm × 35 mm × 20 mm (4.6 in × 1.4 in × 0.8 in)	120 mm × 100 mm × 50 mm (4.7 in × 4 in × 2 in)
Mounting:	Wood, concrete, metal poles Steel bands or bolts	
Applications:	Anchor point for clamps (single/double)	Anchor point for clamps Horizontal support: up to 3 clamps Drop: up to 5 clamps

OSP Hooks	269-OPH30-011P5
	  
Load capacity:	1.5 kN (~340 lbf)
Material:	Galvanized steel
Dimensions:	65 mm × 65 mm × 55 mm (4.6 in × 1.4 in × 0.8 in)
Mounting:	Wood, concrete, metal poles Steel bands or screws
Applications:	Anchor point for clamps