

# OPTICAL FIBER RACK-MOUNT PANEL LGX | 3-POSITION | 1 RMU



## DESCRIPTION

Optical Fiber Rack-Mount Panel, LGX,  
Three-Position, 1 RMU

## FEATURES

- Standard 19 in. rack/cabinet mount
- 1 RMU
- Holds three LGX adapter plates
- Black powder-coated finish
- 1 × Panel with integral cable management
- 1 × Set of mounting screws
- 1 × Shipping box
- EIA-ECA-310-E compliant



## 266-PMD01-1A3A

Height	Width	Depth (Panel Frame)	Depth (with CMB)	Color	Weight
1.75 in. (44.45 mm)	19 in. (482.6 mm)	0.6 in. (15.24 mm)	5 in. (127 mm)	Black	0.6 lb (0.27 mm)

## CHARACTERISTICS

Form-Factor:	19 in. rack/cabinet mounting standard (EIA-ECA-310-E)
Capacity:	Three LGX Adapter Plates; Up to 72 optical fibers
Materials:	0.06 in. (1.5 mm) (16-GA) CRS; Black powder coating
Cable Management:	Set of USCU fasteners; 4 × #10-32 × 5/8 cross-recessed pan-head machine screws, black; 4 × #12-24 × 5/8 cross-recessed pan-head machine screws, black; 4 × #12 × 9/16 × 3/8 plain round washers, nylon, black

## ENVIRONMENTAL

Operating Temperature:	-20 °C—+70 °C (-4 °F—+158 °F)
Operating Humidity:	≤95 % RH non-condensing

## WEIGHT

0.6 lb. (0.25 kg)  
without cable management



**\*IN PICTURE SHOWN: LOADED ADAPTER PLATES ARE AN EXAMPLE AND  
SOLD SEPARATELY - PART #'S: 264-LAP042C6Y1**

**VERTICAL CABLE**

951.696.7772 California  
800.749.2447 Florida  
845.391.8318 New York  
713.322.7242 Texas

[verticalcable.com](http://verticalcable.com)

Rev. 12/2025

Subject to change without notice.