



VERTICAL CABLE

## DESCRIPTION

**Optical Fiber Wall-Mount Enclosure, Standard-Series, Single-Door, LGX, Two-Position, Latch**

## FEATURES

- Holds two (2) LGX adapter plates (up to 48 fibers)
- Durable 16-GA CRS, Black Powder-Coated Finish
- Latch lock
- Cable management: Grommeted entry points; perforated cable anchor plates; strength elements anchor points (screw joints); set of cable ties and self-gripping tie wraps
- Fiber management: Spools, rings
- Weight: 3 lb. (1.36 kg)



# OPTICAL FIBER WALL-MOUNT ENCLOSURE SINGLE DOOR | TWO-POSITION

**268-STD01-1B1**

## CHARACTERISTICS

Materials: 0.06 in. (1.5 mm) (16-GA) CRS;  
Black Powder Coating  
Mounting: Surface/wall  
Doors: One door; opens sideways

## CAPACITY

Adapter Plates: Two LGX Adapter Plates;  
Optical Fibers: Up to 48 optical fibers  
Splice Trays: Up to two 24-fiber splice trays;

## ENVIRONMENTAL

Operating Temperature: -20 °C to +70 °C (-4 °F to +158 °F)  
Operating Humidity: ≤95 % RH non-condensing

## DIMENSIONS

Height:	11.8 in. (300 mm)
Width:	13.8 in. (350 mm)
Depth:	2.6 in. (65 mm)

## VERTICAL CABLE ACCESSORIES

1. 265-CAS01-1B200 (compact cassettes)
2. 265-CAS01-2B200 (standard cassettes)
3. 264-LAP Series



\*Accessories NOT INCLUDED

Florida (HQ)  
800-749-2447

California  
951-696-7772

New York  
845-391-8318

Texas  
713-322-7242

[verticalcable.com](http://verticalcable.com)

This specification sheet is subject to change without notice.

Rev. 01/2026