



VERTICAL CABLE

# OPTICAL FIBER WALL-MOUNT ENCLOSURE

## SINGLE DOOR | FOUR-POSITION

### 268-STD01-1D1

### DESCRIPTION

Optical Fiber Wall-Mount Enclosure, Standard-Series, Single-Door, LGX, Four-Position, Latch

### FEATURES

- Holds four (4) LGX adapter plates (up to 96 fibers)
- Durable 16-GA CRS, Black Powder-Coated Finish
- Latch lock
- Cable management: Grommated entry points; perforated cable anchor plates; strength elements anchor points (screw joints); set of cable ties and self-gripping tie wraps
- Fiber management: Spools, rings
- Weight: 9.5 lb. (4.3 kg)



### CHARACTERISTICS

Materials: 0.06 in. (1.5 mm) (16-GA) CRS; Black Powder Coating

Mounting: Surface/wall

Doors: One door; opens sideways

### CAPACITY

Adapter Plates: Four LGX Adapter Plates;

Optical Fibers: Up to 96 optical fibers

Splice Trays: Up to four 24-fiber splice trays;

### ENVIRONMENTAL

Operating Temperature: -20 °C–+70 °C (-4 °F–+158 °F)

Operating Humidity: ≤95 % RH non-condensing

### DIMENSIONS

|         |                   |
|---------|-------------------|
| Height: | 11.8 in. (300 mm) |
| Width:  | 13.8 in. (350 mm) |
| Depth:  | 3.4 in. (85 mm)   |

### VERTICAL CABLE ACCESSORIES

1. 265-CAS01-1B200 (compact cassettes)
2. 265-CAS01-2B200 (standard cassettes)
3. 264-LAP Series



\*Accessories NOT INCLUDED

Florida (HQ)  
800-749-2447

California  
951-696-7772

New York  
845-391-8318

Texas  
713-322-7242

[verticalcable.com](http://verticalcable.com)

This specification sheet is subject to change without notice.

Rev. 01/2026