



VERTICAL CABLE

DESCRIPTION

Optical Fiber Wall-Mount Enclosure, Standard-Series, Dual-Door, LGX, Four-Position, Lock/Latch

FEATURES

- Holds four (4) LGX adapter plates (up to 96 fibers)
- Durable 16-GA CRS, Black Powder-Coated Finish
- Latch lock
- Cable management: Grommeted entry points; perforated cable anchor plates; strength elements anchor points (screw joints); set of cable ties and self-gripping tie wraps
- Fiber management: Spools, rings
- Weight: 12 lb. (5.44 kg)



OPTICAL FIBER WALL-MOUNT ENCLOSURE DUAL DOOR | FOUR-POSITION

268-STD02-1D12

CHARACTERISTICS

Materials: 0.06 in. (1.5 mm) (16-GA) CRS;
Black Powder Coating
Mounting: Surface/wall
Doors: Two doors;
1st: latch, opens sideways
2nd: lock: opens downward

CAPACITY

Adapter Plates: Four LGX Adapter Plates;
Optical Fibers: Up to 96 optical fibers
Splice Trays: Up to four 24-fiber splice trays;

ENVIRONMENTAL

Operating Temperature: -20 °C–+70 °C (-4 °F–+158 °F)
Operating Humidity: ≤95 % RH non-condensing

DIMENSIONS

Height:	11.4 in. (290 mm)
Width:	14.2 in. (360 mm)
Depth:	4.1 in. (105 mm)

VERTICAL CABLE ACCESSORIES

1. 265-CAS01-1B200 (compact cassettes)
2. 265-CAS01-2B200 (standard cassettes)
3. 264-LAP Series



*Accessories NOT INCLUDED

Florida (HQ)
800-749-2447

California
951-696-7772

New York
845-391-8318

Texas
713-322-7242

verticalcable.com

This specification sheet is subject to change without notice.

Rev. 01/2026