



VERTICAL CABLE

# OPTICAL FIBER OSP SPLICE CLOSURE

HORIZONTAL | 96 FIBER CAPACITY | 6-PORT

## 265-OSC00-09606

### DESCRIPTION

**OSP Splice Closure, Horizontal, In-line, 6 Cable Entry Ports, Up to 96 Fibers, IP68, UV resistant**

### FEATURES

- Horizontal In-Line Design
- 6-Port Entry System
- Weather-Resistant & Sealed Construction
- High-Capacity Splice Tray Support
- Tool-Free Resealing
- UV-Resistant Housing
- Weight: 6.1 lbs. - 7.1 lbs. (2.75 kg - 3.2 kg)



### CHARACTERISTICS

Fiber Capacity: 96 Fiber  
 Cable Entry Ports: 6  
 Splice Cassettes: 8 x 12F  
 Cable Diameter Range: 0.32 in. - 0.91 in. (8 mm - 23 mm)  
 Material: High-Impact Fiber-Reinforced PC

### DIMENSIONS

Height:	4.3 in. (110 mm)
Width:	8.7 in. (220 mm)
Depth:	17.7 in. (450 mm)

### ENVIRONMENTAL

Operating Temperature: -40 °F±149 °F (-40 °C±65 °C)  
 Environmental Protection: IP68  
 Radiation Protection: UV Resistant



Florida (HQ)  
800-749-2447

California  
951-696-7772

New York  
845-391-8318

Texas  
713-322-7242

[verticalcable.com](http://verticalcable.com)

This specification sheet is subject to change without notice.

Rev. 03/2026