



VERTICAL CABLE

OPTICAL FIBER OSP SPLICE CLOSURE

HORIZONTAL | 96 FIBER CAPACITY | 8-PORT

265-OSC00-09608

DESCRIPTION

OSP Splice Closure, Horizontal, In-line,
8 Cable Entry Ports, Up to 96 Fibers, IP68,
UV resistant

FEATURES

- Horizontal In-Line Design
- 8-Port Entry System
- Weather-Resistant & Sealed Construction
- High-Capacity Splice Tray Support
- Tool-Free Resealing
- UV-Resistant Housing
- Weight: 6.1 lbs. - 7.1 lbs. (2.75 kg - 3.2 kg)



CHARACTERISTICS

Fiber Capacity: 96 Fiber
 Cable Entry Ports: 8
 Splice Cassettes: 8 x 12F
 Cable Diameter Range: 0.32 in. - 0.91 in. (8 mm - 23 mm)
 Material: High-Impact Fiber-Reinforced PC

DIMENSIONS

| | |
|---------|-------------------|
| Height: | 4.3 in. (110 mm) |
| Width: | 8.7 in. (220 mm) |
| Depth: | 17.7 in. (450 mm) |

ENVIRONMENTAL

Operating Temperature: -40 °F±149 °F (-40 °C±65 °C)
 Environmental Protection: IP68
 Radiation Protection: UV Resistant



Florida (HQ)
800-749-2447

California
951-696-7772

New York
845-391-8318

Texas
713-322-7242

verticalcable.com

This specification sheet is subject to change without notice.

Rev. 03/2026