



VERTICAL CABLE

# OPTICAL FIBER OSP SPLICE CLOSURE

VERTICAL | 48 FIBER CAPACITY | 4-PORT

## 265-OSC10-04804

### DESCRIPTION

OSP Splice Closure, Vertical, Dome,  
4 Cable Entry Ports, Up to 48 Fibers, IP68,  
UV Resistant

### FEATURES

- Vertical Dome Design
- 4-Port Entry System
- Weather-Resistant & Sealed Construction
- High-Capacity Splice Tray Support
- Tool-Free Resealing
- UV-Resistant Housing
- Weight: 4 lbs. - 4.2 lbs. (1.8 kg - 1.9 kg)



### CHARACTERISTICS

Fiber Capacity: 48 Fiber  
 Cable Entry Ports: 4  
 Splice Cassettes: 4 × 12F  
 Cable Diameter Range: 0.32 in. - 0.63 in. (8 mm - 16 mm)  
 Material: High-Impact Fiber-Reinforced PC

### DIMENSIONS

Height:	11.4 in. (290 mm)
Width:	7.1 in. (180 mm)

### ENVIRONMENTAL

Operating Temperature: -40 °F±149 °F (-40 °C±65 °C)  
 Environmental Protection: IP68  
 Radiation Protection: UV Resistant



Florida (HQ)  
800-749-2447

California  
951-696-7772

New York  
845-391-8318

Texas  
713-322-7242

[verticalcable.com](http://verticalcable.com)

This specification sheet is subject to change without notice.

Rev. 03/2026