VERTICAL CABLE

AUDIO CABLE
16 AWG 2 CONDUCTORS
STRANDED (UNSHIELDED)

209-2317

DESCRIPTION

Audio Cable, Unshielded, 16 AWG 2 Conductor Stranded Bare Copper, 1000 ft., Wooden Spool, White

FEATURES

- Conductor: Stranded Bare Copper
- Riser (CMR), CL3R rated
- Sequential Length Markings on Jacket
- ETL-listed, RoHS-Compliant
- 1000 ft. Wooden Spool

APPLICATIONS

- Intercom Systems
- Sound / Audio Systems
- Indoor Applications



CONSTRUCTION

Conductor Count:	2
Shape:	Round
Rip Cord:	Yes

CONDUCTORS

	Stranded Bare Copper
Trade Size:	16 AWG
Stranding:	65/0.16 mm

INSULATION

	Polyvinyl Chloride (PVC)
Outer Diameter:	0.08 in. (2.10 mm)
Insulation Color:	Red, Black

JACKET

	Polyvinyl Chloride (PVC)
Average Thickness:	0.02 in. (0.51 mm)
Outer Diameter:	0.20 in. (5.10 mm)
Marking:	VERTICAL 5024318 c(ETL)us AUDIO CABLE 16AWG 2 COND 65 STRANDED OXYGEN FREE CMR FT4 CL3R RoHS V2094P400449 XXXXFT 091506P0707208

MECHANICAL

Temperature Rating:	75° C
Aging Condition (°Cxhrs):	100x168
Tensile Strength (Mpa)	
Before:	≥13.8
After:	≥85% of unaged
Aging Elongation (%)	
Before:	≥100
After:	≥50% of unaged
Cold Bend (-20±2°Cx4hrs):	No Crack


SAFETY

Voltage Rating:	300 V RMS
NFPA 70 (NEC ®)Rating:	CMR/CL3R

DIMENSIONS

Length:	13.5 in. (343 mm)
Width:	13.5 in. (343 mm)
Height:	7 in. (177.8 mm)
Weight:	30 lbs (spool)





Florida (HQ) 800-749-2447
California 951-696-7772
New York 845-391-8318
Texas 713-322-7242

verticalcable.com

This specification sheet is subject to change without notice.

RoHS Intertek

Rev. 11/2026